

Dräger X-plore® 8000 Powered Air-Purifying Respirator (PAPR)

Challenging workplace conditions demand reliable solutions. The Dräger X-plore® 8000 offers a new level of intuitive handling combined with intelligent electronics that provide the high degree of safety your people need to focus on the task at hand.



ROBUST: DESIGNED FOR DAILY USE IN TOUGH ENVIRONMENTS

Let's face it: for your workplace, only the most rugged design will do. The Dräger X-plore® 8000 features heavy-duty design with rubber protectors and high ingress protection (IP 65) against dust and water jets from any direction. Two battery versions incorporating the latest Li-ion battery technology provide power for at least 4 h or 8 h, respectively. Protected air intake openings ensure that sparks or water coming from the front will not be sucked into the filter.

COMFORTABLE: LET THE USER FOCUS ON THE TASK

The Dräger X-plore 8000 lets your employees do their job and forget about the PAPR they need for proper personal protection. The advanced carrying system ensures optimal distribution of the weight. The system provides a tight and stable connection between the belt and the unit through a special adaptor plate; a comfort pad is also available as an option. The hose connector features a 360° click adaptor. New headpieces are designed for optimal airflow and maximum comfort to avoid unpleasant eye irritation.

SAFE: SELF-EXPLANATORY OPERATION MINIMISES USER ERROR

The unit recognises connected headgear and automatically selects the correct minimum flow rate, avoiding leakages caused by insufficient flow rates. An optical sensor prevents use without the filter and supports the right display of the saturation of the particle filter at any time. The filter system features plug-and-go exchange. In addition to the optical and acoustical alarm, the unit is also equipped with a vibration alarm. The entire system features uniform colour codes on all exchangeable elements and an error-proof hose connector.

EASY TO MAINTAIN: EFFICIENT CLEANING TOGETHER WITH SECURE OPERATION

The Dräger X-plore 8000 was designed to be practically maintenance free, leading to low cost of ownership. The self-check and self-adjustment systems feature advanced temperature and pressure sensor technology to ensure the right flow rate for any environment. The simple and efficient charging system allows rapid charging (under 4h for an empty battery). The unit is designed for fast and easy disassembly for cleaning. The belt and the comfort pad can be easily removed and are both machine-washable.



Dräger X-plore® 8000
Powered Air-Purifying Respirator

As tough as your work.

As safe as possible.



D-118978-2013

Intelligent alarm system
two-step alarm concept with differentiation of risk level

Lithium-ion technology
operating time between 4 and 20 hours depending on the working conditions and system set-up

IP 65 protection
IP 65 for optimal protection and easy decontamination

Filter recognition
advanced sensor technology recognises the correct filter and displays particle filter saturation properly

Hose identification
automatic adjustment of minimum flow rate for attached headpiece



D-55585-2013

Dräger X-plore® 8000 Premium hood, short



D-11292-2010

Dräger X-plore® 8000 Helmet with visor



D-10503-2011

Dräger FPS 7000 Full-face mask

TECHNICAL DATA

Powered Air-Purifying Respirator for protection against a wide range of gases, dust and particles

Approvals	EN 12941 with Dräger X-plore® 8000 Hoods, Helmets and Visors EN 12942 with Dräger X-plore® 4740/6000 half and full-face masks incl. Dräger FPS 7000 full-face mask
Ingress protection	IP65 (dust-tight and resistant to water jets from all sides)
Airflow	Adjustable in three levels (automatic setting of operating type: loose- or tight-fitting headpiece) Half and full-face mask: 115, 130 or 145 l/min Hoods, Helmets and Visors: 170, 190 or 210 l/min
Battery technology	Lithium-ions: 12.6 V/3.4 Ah (standard battery), 12.6 V/6.8 Ah (high-capacity battery)
Operating time**	Standard battery life: 4 hours (at 210 l/min and P3 filter) High-capacity battery: 8 hours (at 210 l/min and P3 filter)
Charging time	Under 4 hours (in two hours 80 % can be reached)
Weight	Approx. 1,340 g (Dräger X-plore® 8500 incl. standard battery and splash guard lid)
Alarm system	Optical alarm (operating display) Acoustical alarm (≥ 80 dB(A) at 1 m) Vibration alarm
Belt length	Adjustable between 750 mm and 1,400 mm (standard and decontamination version)
Belt extension	350 mm (standard and decontamination version)

** Depending on the adjusted flow and the concentration of contaminants

MODULAR: A WIDE RANGE OF COMPONENTS FOR EVERY APPLICATION

The Dräger X-plore 8000 offers a number of user-friendly standard and specialised carrying systems for standard and decon-

tamination applications. Dräger has also developed a wide range of tight- and loose-fitting headgear such as half and full-face masks, short and long hoods and helmets with visor and protective visor. Standard

and enhanced flexibility hoses are available and compatibility is ensured. Components and accessories can be combined to best fit your application, and system upgrades are possible at any time.

ACCESSORIES



D-95635-2013

Dräger X-plore® 8000 Comfort pad



D-119068-2013

Dräger X-plore® 8000 Flexible hose



D-118961-2013

Dräger X-plore® 8000 Storage box

ORDER INFORMATION

			ORDER NUMBER	
Blower unit		Dräger X-plore® 8500 (IP)	R 59 500	
Batteries		Dräger X-plore® 8000 Standard battery	R 59 565	
		Dräger X-plore® 8000 High-capacity battery	R 59 585	
Charger		Dräger X-plore® 8000 Standard charger	R 59 580	
Carrying systems		Dräger X-plore® 8000 Standard belt	R 59 700	
		Belt extension for X-plore® 8000 Standard belt, 35 cm	R 59 750	
		Dräger X-plore® 8000 Comfort pad	R 59 730	
		Dräger X-plore® 8000 Decon belt	R 59 710	
		Belt extension for X-plore® 8000 Decon belt, 35 cm	R 59 760	
	Breathing hoses	Standard hoses	Dräger X-plore® 8000 Standard hose (for Tight-fitting headpieces)	R 59 630
			Dräger X-plore® 8000 Standard hose (for Hoods)	R 59 620
		Dräger X-plore® 8000 Standard hose (for Helmets and Visors)	R 59 640	
Flexible hoses		Dräger X-plore® 8000 Flexible hose (for Tight-fitting headpieces)	R 59 610	
		Dräger X-plore® 8000 Flexible hose (for Hoods)	R 59 600	
		Dräger X-plore® 8000 Flexible hose (for Helmets and Visors)	R 59 650	
Filter	EN - P	Dräger X-plore® 8000 Filter P R SL	67 39 535	
	EN - A2 (gas filter)	Dräger X-plore® 8000 Filter A2	67 39 580	
	EN - A2 P (combination filter)	Dräger X-plore® 8000 Filter A2 P R SL	67 39 545	
	EN - ABEK1 Hg P (combination filter)	Dräger X-plore® 8000 Filter A1B1E1K1 Hg P R SL	67 39 555	
Hoods	Standard hoods	Dräger X-plore® 8000 Standard hood, short (S/M)	R 59 800	
		Dräger X-plore® 8000 Standard hood, short (L/XL)	R 59 810	
		Dräger X-plore® 8000 Standard hood, long (S/M)	R 59 820	
		Dräger X-plore® 8000 Standard hood, long (L/XL)	R 59 830	
	Premium hoods	Dräger X-plore® 8000 Premium hood, short (S/M)	R 59 840	
		Dräger X-plore® 8000 Premium hood, short (L/XL)	R 59 850	
		Dräger X-plore® 8000 Premium hood, long (S/M)	R 59 860	
		Dräger X-plore® 8000 Premium hood, long (L/XL)	R 59 870	
		Half masks	Dräger X-plore® 4740 SI (S/M)	R 55 875
			Dräger X-plore® 4740 SI (M/L)	R 55 874
Full-face masks	Dräger X-plore® 6300 EPDM/PMMA	R 55 800		
	Dräger X-plore® 6530 EPDM/PC	R 55 795		
	Dräger X-plore® 6570 SI/PC	R 55 790		
	Dräger FPS 7000 EPDM-S1-PC-CR	R 56 502		
	Dräger FPS 7000 EPDM-M2-PC-CR	R 56 310		
Helmets	Dräger FPS 7000 EPDM-L2-PC-CR	R 56 503		
	Dräger X-plore® 8000 Helmet with visor, white	R 59 910		
	Dräger X-plore® 8000 Helmet with visor, black	R 58 325		
	Dräger X-plore® 8000 Protective visor	R 59 900		
Accessories		Dräger X-plore® 8000 Storage box	R 59 690	

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53-55
23558 Lübeck, Germany

www.draeger.com

Manufacturer:

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany

AUSTRALIA

Dräger Safety Pacific Pty. Ltd.
8 Acacia Place
Notting Hill VIC 3168
Toll-free +61 1800 DRAGER
(1800 372 437)
Fax +61 1800 64 74 84
customer.service@draeger.com

CANADA

Draeger Safety Canada Ltd.
2425 Skymark Ave
Mississauga, Ontario, L4W 4Y6
Tel +1 905 821 8988
Toll-free +1 877 Drager 1
(+1 877 372 4371)
Fax +1 905 821-2565
Toll-free Fax +1 800 329 8823

P. R. CHINA

Draeger Safety Equipment
(China) Co., Ltd.
A22 Yu An Rd, B Area,
Tianzhu Airport Industrial Zone,
Shunyi District, Beijing 101300
Tel +86 10 80 49 80 00
Fax +86 10 80 49 80 05

FRANCE

Dräger Safety France SAS
3c route de la Fédération, BP 80141
67025 Strasbourg Cedex 1
Tel +33 3 88 40 76 76
Fax +33 3 88 40 76 67

MEXICO

Draeger Safety S.A. de C.V.
Av. Peñuelas No. 5 Bodega No. 37
Fraccionamiento Industrial
San Pedrito
Querétaro, Qro México
Tel +52 442 246-1113
Fax +52 442 246-1114

NETHERLANDS

Dräger Safety Nederland B.V.
Edisonstraat 53
2700 AH Zoetermeer
Tel +31 79 344 46 66
Fax +31 79 344 47 90

REGION ASIA PACIFIC

Dräger Safety Asia Pte Ltd.
67 Ayer Rajah Crescent #06-03
Singapore 139950
Tel +65 68 72 92 88
Fax +65 65 12 19 08

REGION CENTRAL

AND SOUTH AMERICA
Dräger Panama S. de R.L.
Complejo Business Park,
V tower, 10th floor
Panama City
Tel +507 377-9100
Fax +507 377-9130
contactcsa@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

SPAIN

Dräger Safety Hispania S.A.
Calle Xaudaró 5
28034 Madrid
Tel +34 91 728 34 00
Fax +34 91 729 48 99

UNITED KINGDOM

Draeger Safety UK Ltd.
Blyth Riverside
Business Park
Blyth, Northumberland
NE24 4RG
Tel +44 1670 352-891
Fax +44 1670 356-266

USA

Dräger Safety, Inc.
101 Technology Drive
Pittsburgh, PA 15275
Tel +1 412 787 8383
Fax +1 412 787 2207